

Map tiles

Patrick Brown

April 9, 2014

The following are some examples of maps produced with
`mymap=openmap(x, path="something")`

```
1 plot (openmap(x,path=" osm "))
```



```
2 plot (openmap(x,path=" osm-no-labels "))
```



3 `plot (openmap(x,path=" osm-transport "))`



4 `plot (openmap(x,path=" bw-mapnik "))`




5 `plot RGB (openmap(x,path=" mapquest "))`




```
6 plot RGB (openmap(x,path=" mapquest-sat "))
```



```
7 plot (openmap(x,path=" landscape "))
```



```
8 plot (openmap(x,path=" opentopomap "))
```


opentopomap is
not currently
available



```
9 plot (openmap(x,path=" maptoolkit "))
```



```
10 plot (openmap(x,path=" waze "))
```



```
11 plot (openmap(x,path=" mapbox "))
```

mapbox is
not currently
available


```
12 plot (openmap(x,path=" humanitarian "))
```



```
13 plot (openmap(x,path=" parking-bw "))
```




```
14 plot (openmap(x,path=" osm-locale-de "))
```



```
15 plot (openmap(x,path=" bw-noicons "))
```



```
16 plot (openmap(x,path=" osm-labels-en "))
```




```
17 plot (openmap(x,path=" osm-labels-fr "))
```



```
18 plot (openmap(x,path=" osm-labels-de "))
```




```
19 plot (openmap(x,path=" osm-labels-it "))
```



```
20 plot (openmap(x,path=" osm-labels-es "))
```



21 `plot (openmap(x,path=" osm-labels-ru "))`



22 `plot (openmap(x,path=" stamen-toner "))`



23 `plot RGB (openmap(x,path=" stamen-watercolor "))`

